

DRAWING LEGEND	
RESTORATION LEGEND	
SYMBOL	DESCRIPTION
	ASPHALT PAVEMENT
	CONCRETE PAVEMENT
	CONCRETE CURB AND GUTTER
	CONCRETE PANELS
	BRICK SIDEWALK
	REPLANT EX. TREE
	REINSTALL EX. SIGN
	REINSTALL EX. LIGHT POLE
	REINSTALL EX. FIRE HYDRANT
	CONCRETE CURB

- NOTE:
1. RECONNECT EXISTING SITE LIGHTING TO REINSTALLED SITE LIGHTING USING NEW CONDUCTORS.
  2. SECURE TRASH CAN WITH 2- 3/8" DIAMETER, 6" LONG STAINLESS STEEL EXPANSION ANCHORS.

All Restoration work within Hatch area to be provided by separate UMB project. Bidder will only provide backfill and temporary stabilization (including seed and mulch) and protection (e.g. construction fencing) until project is ready to begin work.

Curb to be restored under electrical project (typ.)

Carefully remove and salvage ex. blue light pole. Return to Owner for installation by others under separate UMB project

Carefully remove and salvage ex. light pole. Return to Owner for installation by others under separate UMB project (typ. for 3)

RESTORATION PLAN

SCALE: 1" = 10'

